

# Montaplast B

## Butyl-rubber waterproofing foil

### ■ Description

Bitumen rubber based, waterproofing foil backed with fleece on both sides for supporting joints, wall to wall and wall to floor corners on substrates.

### ■ Advantages

- Support for water tightness of delicate points.
- Flexibility and resistance to rip.
- Applicable in the desired size and form upon cutting.
- Applicable with polymer-bitumen based, epoxy and cement based products.
- Two-side backed with fleece.

### ■ Range of application

- Used in waterproofing applications to be performed with polymer-bitumen modified waterproofing materials, cement based waterproofing slurries, epoxy based waterproofing materials for supporting water tightness of delicate points such as joints on the substrates of buildings that contact earth, wall to wall and wall to floor edges and drains.

### ■ Performance

- Thickness of material: approx. 0,5 mm
- Width: 1 m
- Weight of substrate: approx. 500 gr/m<sup>2</sup>
- Max. bending under constant loading: approx. 25 %
- Resistance to heat: approx. +90 °C

### ■ Application

- Upon the first coat application of waterproofing material used on the entire substrate, 30-50 cm width **Montaplast B** waterproofing foil, which is prepared by cutting according to the dimensions of application area, is placed on the substrate when waterproofing material is still wet.
- Second coat waterproofing material is applied in a way to cover the whole substrate where **Montaplast B** waterproofing foil has been placed.
- In the applications where vertical and horizontal joints are together, **Montaplast B** waterproofing foil should be primarily applied to horizontal points and vertical application should be performed on such application.

### ■ Packaging

50 ml roll.

### ■ Shelf life

2 years from the production date if stored by protecting against UV effect.

> The stated times apply for 20 °C substrate and ambient temperature and increase at lower temperatures and decrease at high temperatures.

> **Saint-Gobain Weber Yapı Kim. San. ve Tic. A.Ş.** is not responsible for the application errors arising from use of product beyond its intended purpose or failure to comply with the foregoing application conditions and advice on the product.



Saint-Gobain Weber  
Yapı Kimyasalları San. ve Tic. A.Ş.  
Ankara Karayolu 26. Km.  
35171 Kemalpaşa • İzmir • Türkiye

Tel : +90 (232) 397 07 00  
Fax : +90 (232) 397 08 00  
www.weber.com.tr  
info@weber.com.tr



Weber products are produced at ISO 9001:2008 Quality Management System Certified production facilities.