

weber FP 100

Tile protector

■ Description

Acrylic emulsion based tile protector.

■ Range of application

- Applied for the purpose of protecting materials such as granite, ceramic, natural stone sensitive to stains especially before dark-color grout application.

■ Application substrates

- Interior and exterior floors and walls;
 - Ceramic,
 - Granite ceramic,
 - Coating materials such as granite, natural composed stone, etc.
- Please consult us for all other application substrates.

■ Conditions of application

- Ambient temperature is between +5 °C and +30 °C.
- Avoid application in very damp and/or hot weather.

■ Preparation of substrates

- Coatings should be free from dust before application of **weber FP 100**.

■ Application

- **weber FP 100** should be applied without thickening via a sponge or roller before grout application.
- 10 minutes after the first coat, the second coat of **weber FP 100** should be applied.
- The application of grout can start after the substrate is left for drying for further 10 minutes.

■ Attention points

- The substrate should be cleaned with a damp sponge within maximum 2 hours after the grout application.

■ Limits of application

Should not be applied on dirty, greasy substrates.

■ Consumption

35 ml/m².

■ Packaging

0,5 l plastic drum.

■ Color

Transparent.

■ Application tools

Sponge, roller.

■ Shelf life

1 year as of the production date in dry and moisture-free environment provided that packages will not be opened. Package should be kept tightly closed when not in use. Package should be protected against frost.

> The stated times apply for 20 °C substrate and ambient temperature and increase at lower temperatures and decrease at high temperatures.

> **Saint-Gobain Weber Yapı Kim. San. ve Tic. A.Ş.** is not responsible for the application errors arising from use of product beyond its intended purpose or failure to comply with the foregoing application conditions and advice on the product.



Saint-Gobain Weber
Yapı Kimyasalları San. ve Tic. A.Ş.
Ankara Karayolu 26. Km.
35171 Kemalpaşa • İzmir • Türkiye

Tel : +90 (232) 397 07 00
Fax : +90 (232) 397 08 00
www.weber.com.tr
info@weber.com.tr



Weber products are
produced at ISO 9001:2008
Quality Management
System Certified
production facilities.

