

# weber.deko elit

## Silicone added, acrylic interior paint

### ■ Description

Acrylic-based, silicon-added, final coat mat interior paint.

### ■ Advantages

- Allows the substrate to breath.
- Water-repellant.

### ■ Range of application

- Used on interiors of all buildings for the decorative purpose.

### ■ Application substrates

- Interior walls,
  - Cement-based renders;
  - Concrete (**weber.tec R**, **weber.tec RK**, or **weber.tec RM** applied),
  - Plaster render, gypsum block and plaster board substrates,
  - Gas concrete (**weber.tec GB** or **weber.tec RM** applied).
- Please consult us for all other application substrates.

### ■ Reference standards

- TS 5808.

### ■ Application properties

- Drying time: 6-24 hours (at 20 °C ambient temperature).

### ■ Conditions of application

- Ambient temperature is between +5 °C and +30 °C.
- Avoid application in very damp and/or hot weather.

### ■ Preparation of substrates

- The substrate should be clean, dry, smooth and sound.
- Plaster screed, gypsum block and plaster board substrates should be primed with **weber.prim saten** without diluting and application of **weber.deko elit** should be started at least 6 hours later.
- Other substrates should be primed with **weber.prim klasik** diluted in 1/5 (**weber.prim klasik**/water) and application of **weber.deko elit** should be started at least 6 hours later.

### ■ Application

- **weber.deko elit** should be diluted with water in the rate of 30 % for the first and second coat in brush and roller application.
- **weber.deko elit** diluted as necessary should be mixed well until a homogenous state is achieved.
- **weber.deko elit** should be applied to the entire substrate in 2 coats with lambskin roller or roller.
- Wait for minimum 2 hours between coats (at 20 °C ambient temperature).

### ■ Attention points

- Never use salty water.
- Never add lime and similar foreign materials.
- All tools should be cleaned with water after the application before drying.
- **weber.deko elit** should be applied to the substrates on which **weber.tec saten** or satin plaster was applied via felt roller or velvet roller.

### ■ Limits of application

- Not applicable on wooden and metal substrates.
- Not applicable on damp substrates.
- Not applicable on wall paper directly.

### ■ Consumption

6-7 m<sup>2</sup>/l. (For two layers).

### ■ Packaging

Net 15 l. plastic bucket.

### ■ Colour

29 colors.

### ■ Application tools

Lambskin roller, brush.

### ■ Shelf life

2 years as of the production date in dry and moisture-free environment provided that packages will not be opened. Package should be kept tightly closed when not in use. Package should be protected against frost.

➤ The stated times apply for 20 °C substrate and ambient temperature and increase at lower temperatures and decrease at high temperatures.

➤ **Saint-Gobain Weber Yapı Kim. San. ve Tic. A.Ş.** is not responsible for the application errors arising from use of product beyond its intended purpose or failure to comply with the foregoing application conditions and advice on the product.



Saint-Gobain Weber  
Yapı Kimyasalları San. ve Tic. A.Ş.  
Ansızca köyü Ansızca İç Kısım San. Sok. No: 284  
35171 Kemalpaşa • İzmir • Türkiye

Tel : +90 (232) 397 07 00  
Faks : +90 (232) 397 08 00  
www.weber.com.tr  
info@weber.com.tr



Weber products are  
produced at ISO 9001 –  
ISO 14001 – OHSAS 18001  
Management System  
Certified production facilities.

