

weber.deko plastik

Interior wall paint

■ Description

Acrylic-based, interior paint.

■ Advantages

- Allows the substrate to breathe.
- Odorless.
- Economical.

■ Range of application

- Used on interiors of all buildings.

■ Application substrates

- Interior walls;
 - Cement based renders,
 - Concrete (**weber.tec R**, **weber.tec RK**, or **weber.tec RM** applied),
 - Plaster render,
 - Gypsum block and plaster board substrates,
 - Gas concrete (**weber.tec GB** or **weber.tec RM** applied).
- Old painted substrates.
- Please consult us for all other application substrates.

■ Reference standards

- TS 5808.

■ Application properties

- Drying time: 6-24 hours.

■ Conditions of application

- Ambient temperature is between +5 °C and +30 °C.
- Avoid application in very damp and/or hot weather.

■ Preparation of substrates

- The substrate should be clean, dry, smooth and sound.
- Plaster screed, gypsum block and plaster board substrates should be primed with **weber.prim saten** without diluting and application of **weber.deko plastik** should be started at least 6 hours later.
- Other substrates should be primed with **weber.prim klasik** diluted in 1/5 (**weber.prim klasik**/water) and application of **weber.deko plastik** should be started at least 6 hours later.

■ Application

- **weber.deko plastik** should be diluted with water in the rate of 30 % for the first and second coat in brush and roller application, should be mixed well until a homogenous state is achieved.
- **weber.deko plastik** should be applied to the entire substrate in 2 coats with lambskin roller or brush roller.
- Wait for 2 hours at least between coats.

■ Attention points

- Never use salty water, never add lime and similar foreign materials.
- All tools should be cleaned with water before drying after the application.

■ Consumption

250-300 g/m² (For two layers).

■ Packaging

Net 20 kg plastic bucket.

■ Colour

21 colors.

■ Application tools

Lambskin roller, brush.

■ Shelf life

1 year as of the production date in dry and moisture-free environment provided that packages will not be opened. Package should be kept tightly closed when not in use. Package should be protected against frost.

> The stated times apply for 20 °C substrate and ambient temperature and increase at lower temperatures and decrease at high temperatures.

> **Saint-Gobain Weber Yapı Kim. San. ve Tic. A.Ş.** is not responsible for the application errors arising from use of product beyond its intended purpose or failure to comply with the foregoing application conditions and advice on the product.



Saint-Gobain Weber
Yapı Kimyasalları San. ve Tic. A.Ş.
Ansızca köyü Ansızca İç Kısım San. Sok. No: 284
35171 Kemalpaşa • İzmir • Türkiye

Tel : +90 (232) 397 07 00
Faks : +90 (232) 397 08 00
www.weber.com.tr
info@weber.com.tr



Weber products are
produced at ISO 9001 –
ISO 14001 – OHSAS 18001
Management System
Certified production facilities.

