

# weber.floor 4720 (maxit Floor 4720)

## Transparent water-based surface hardener for cement-based industrial floors

### ■ Description

One-component, low-viscosity, water-based alkaline silicate solution with hardening effect.

### ■ Advantages

- Enables hard substrates with almost no change in floor appearance,
- Water-impermeability,
- High water vapor permeability,
- Resistant to high temperatures.
- Easy application.

### ■ Range of application

- Applied for reinforcing cement-based substrates dusting and having high absorptivity in interior and exterior areas.

### ■ Application substrates

- Interior and exterior;
  - Warehouses,
  - Workshops,
  - Service stations,
  - Industrial building floors,
  - Houses,
  - Offices.

### ■ Conditions of application

- Ambient temperature is between +5 °C and +30 °C.
- Avoid application in very damp and/or hot weather, strong wind or sun.
- It should not be used on substrates which are frozen or melting or have the risk of frost and rain within 24 hours.

### ■ Preparation of substrates

- The substrate should be clean and dry. It should be free from dust, mud, loose particles, grease and other contaminants.

### ■ Application

- Application of **weber.floor 4720** can be done in 1 or 2 coats based on the condition of substrate.
- Application can be done with roller or brush. You should not allow deposits and you should spread the material homogeneously.
- Glass and aluminum based substrates should be protected during application, if there are splashing points, they should be cleaned with water immediately.

### ■ Attention points

- The substrate should be protected against water for minimum 24 hours after the application.
- **weber.floor 4720** is not applied on substrates that synthetic resin products were applied.

### ■ Consumption

- On floor screeds: 0,10-0,15 kg/m<sup>2</sup>
- On concrete: 0,15-0,30 kg/m<sup>2</sup>.

### ■ Packaging

Net 25 kg plastic drum.

### ■ Color

Transparent.

### ■ Application tools

Brush, roller.

### ■ Shelf life

1 year as of the production date in dry and moisture-free environment.  
Package should be kept tightly closed when not in use.

> The stated times apply for 20 °C substrate and ambient temperature and increase at lower temperatures and decrease at high temperatures.

> **Saint-Gobain Weber Yapı Kim. San. ve Tic. A.Ş.** is not responsible for the application errors arising from use of product beyond its intended purpose or failure to comply with the foregoing application conditions and advice on the product.



Saint-Gobain Weber  
Yapı Kimyasalları San. ve Tic. A.Ş.  
Ankara Karayolu 26. Km.  
35171 Kemalpaşa • İzmir • Türkiye

Tel : +90 (232) 397 07 00  
Fax : +90 (232) 397 08 00  
www.weber.com.tr  
info@weber.com.tr



Weber products are produced at ISO 9001:2008 Quality Management System Certified production facilities.

