

weber.mur spack SF

Interior satin paste

■ Description

Acrylic-based, ready to use interior satin paste.

■ Advantages

- Ensures very smooth appearance before paint application on interiors.
- Improves resistance of surfaces.

■ Range of application

- Used for smooth, texture on the ceilings and internal surfaces of all buildings.

■ Application substrates

- Interior walls;
 - Cement based render
 - Concrete
 - Gypsum board
 - Gypsum render
 - Old painted substrates
- Please consult us for all other application substrates.

■ Preparation of substrates

- The substrate should be clean, dry, smooth and sound.
- Minor defects on the substrate should be repaired with **weber.tec RM** if it is unpainted or with **weber.mur spack** or **weber.tec RM** not mixed with cement.

■ Application

- **weber.mur spack SF** is applied without diluting (it can be diluted with water in compulsory cases).
- It is applied as one layer on slurry or gypsum render applied substrates and as 2 layers in the ceilings.
- Material should be leveled with preferably a wide spatula after applying on the substrate with a spatula or sprayed with machine.
- Other layers are applied similarly following drying of the first coat.
- The material is sanded after drying completely and made ready for paint or wall paper applications.

■ Consumption

- 0,8 kg/m² (for single layer).

■ Packaging

Net 25 kg plastic bucket.

■ Color

White.

■ Application tools

Spatula, trowel.

■ Shelf life

1 year as of the production date in dry and moisture-free environment provided that packages will not be opened. Package should be kept tightly closed when not in use. Package should be protected against frost.

> The stated times apply for 20 °C substrate and ambient temperature and increase at lower temperatures and decrease at high temperatures.

> **Saint-Gobain Weber Yapı Kim. San. ve Tic. A.Ş.** is not responsible for the application errors arising from use of product beyond its intended purpose or failure to comply with the foregoing application conditions and advice on the product.



Saint-Gobain Weber
Yapı Kimyasalları San. ve Tic. A.Ş.
Ankara Karayolu 26. Km.
35171 Kemalpaşa • İzmir • Türkiye

Tel : +90 (232) 397 07 00
Fax : +90 (232) 397 08 00
www.weber.com.tr
info@weber.com.tr



Weber products are produced at ISO 9001:2008 Quality Management System Certified production facilities.