

weber.prim EG

Façade primer

■ Description

Acrylic emulsion based, façade primer with fillings.

■ Range of application

- Applied as a primer on substrates especially with high porosity and absorptivity of which are high in exterior walls of buildings, under ready decorative renders and coating for the purpose of increasing adherence and reducing consumption of final coat ready-made render or coating.

■ Application substrates

- Cement based renders,
- Concrete (**weber.tec R**, **weber tec RK**, or **weber.tec RM** applied),
- Gas concrete (**weber.tec GB** applied),
- Please consult us for all other application substrates.

■ Application

- **weber.prim EG** is diluted in the ratio of 1/1 (**weber.prim EG** /water) and mixed until it reaches a homogenous state and is applied as one layer with lambskin roller or brush.
- In ready screed or for siding, application of **weber.prim EG** should be started after at least 12 hours.
Note: Diluted **weber.prim EG** should be mixed and kept in homogenous state, and it should not deposit.

■ Limits of application

Not applicable on wet and damp substrates.

■ Consumption

150-200 g/m² (for single coat).

■ Packaging

Net 25 kg buckets.

■ Color

5 colors.

■ Application tools

Lambskin roller, brush.

■ Shelf life

1 year as of the production date in dry and moisture-free environment provided that packages will not be opened. Package should be kept tightly closed when not in use. Package should be protected against frost.

> The stated times apply for 20 °C substrate and ambient temperature and increase at lower temperatures and decrease at high temperatures.

> **Saint-Gobain Weber Yapı Kim. San. ve Tic. A.Ş.** is not responsible for the application errors arising from use of product beyond its intended purpose or failure to comply with the foregoing application conditions and advice on the product.



Saint-Gobain Weber
Yapı Kimyasalları San. ve Tic. A.Ş.
Ansızca köyü Ansızca İç Kısım San. Sok. No: 284
35171 Kemalpaşa • İzmir • Türkiye

Tel : +90 (232) 397 07 00
Faks : +90 (232) 397 08 00
www.weber.com.tr
info@weber.com.tr



Weber products are
produced at ISO 9001 –
ISO 14001 – OHSAS 18001
Management System
Certified production facilities.

