

# weber.prim N

## Ready to use floor primer

### ■ Description

Acrylic emulsion-based, alkali resistant ready to use floor primer for porous and dusting floors.

### ■ Range of application

- Applied to ensure the water and moisture impermeability, to increase the adherence under the floor leveling screeds on floors with high absorptivity of buildings.

### ■ Application substrates

- Cement-based screed;
  - Concrete,
- Please consult us for other application substrates.

### ■ Conditions of application

- Ambient temperature is between +5 °C and +30 °C.
- Avoid application in very damp and/or hot weather, strong wind or sun.

### ■ Application

- **weber.prim N** is a ready to use primer. It should be mixed before application and applied as one layer with roller or brush without diluting.
- Application of leveling screed should be started minimum 30 minutes after the application of **weber.prim N**.

### ■ Limits of application

- Not applicable on wet and damp substrates.

### ■ Consumption

4-6 m<sup>2</sup>/kg depending on substrate.

### ■ Packaging

Net 20 kg drum.

### ■ Color

Transparent.

### ■ Application tools

Roller.

### ■ Shelf life

1 year as of the production date in dry and moisture-free environment.

Package should be kept tightly closed when not in use. Packages should be protected against frost.

> The stated times apply for 20 °C substrate and ambient temperature and increase at lower temperatures and decrease at high temperatures.

> **Saint-Gobain Weber Yapı Kim. San. ve Tic. A.Ş.** is not responsible for the application errors arising from use of product beyond its intended purpose or failure to comply with the foregoing application conditions and advice on the product.



Saint-Gobain Weber  
Yapı Kimyasalları San. ve Tic. A.Ş.  
Ankara Karayolu 26. Km.  
35171 Kemalpaşa • İzmir • Türkiye

Tel : +90 (232) 397 07 00  
Fax : +90 (232) 397 08 00  
www.weber.com.tr  
info@weber.com.tr



Weber products are produced at ISO 9001:2008 Quality Management System Certified production facilities.

