

weber.prim SL

Silicate and silicone-based façade primer

■ Description

Silicate and silicone-based, façade primer with fillings produced with silico-silicate technology.

■ Range of application

- Applied as a primer on substrates especially with high porosity and absorptivity of which are high in exterior walls of buildings, under the silicate and silicon-based paint and coating, for the purpose of increasing adherence with floor and water vapor permeability and reducing consumption of final paint and coating.

■ Application substrates

- Cement based renders,
- Concrete (**weber.tec R**, **weber tec RK** or **weber.tec RM** applied),
- Please consult us for all other application substrates.

■ Application

- **weber.prim SL** is diluted in the ratio of 5/1 (**weber.prim SL** /water) and mixed until it reaches a homogenous state and is applied as one layer with lambskin roller or brush.
 - Paint or coating application should be started at least 12 hours after the application of **weber.prim SL**.
- Note:** Diluted **weber.prim SL** should be mixed and kept in homogenous state, and it should not deposit.

■ Limits of application

Not applicable on wet and damp substrates.

■ Consumption

8-11 m²/lt (for single coat).

■ Packaging

Net 25 lt buckets.

■ Color

5 colors.

■ Application tools

Lambskin roller, brush.

■ Shelf life

1 year as of the production date in dry and moisture-free environment provided that packages will not be opened. Package should be kept tightly closed when not in use. Package should be protected against frost.

> The stated times apply for 20 °C substrate and ambient temperature and increase at lower temperatures and decrease at high temperatures.

> **Saint-Gobain Weber Yapı Kim. San. ve Tic. A.Ş.** is not responsible for the application errors arising from use of product beyond its intended purpose or failure to comply with the foregoing application conditions and advice on the product.



Saint-Gobain Weber
Yapı Kimyasalları San. ve Tic. A.Ş.
Anısızca köyü Anısızca İç Kısım San. Sok. No: 284
35171 Kemalpaşa - İzmir - Türkiye

Tel : +90 (232) 397 07 00
Faks : +90 (232) 397 08 00
www.weber.com.tr
info@weber.com.tr



Weber products are
produced at ISO 9001 –
ISO 14001 – OHSAS 18001
Management System
Certified production facilities.

