

weber.prim TG 5 (Eurolan TG 5)

Adherence improving primer

■ Description

Acrylic dispersion based, one component adherence primer.

■ Advantages

- One component
- Ready to use.
- Feature of protecting wood floors from humidity of tile adhesive.
- Supporting substrate strength in tile applications on tile.

■ Range of application

- Used as primer for the purpose of improving surface adherence before tile adhesive in all renovations.

■ Application substrates

- Interior and exterior wall;
 - All types of tiles,
 - Painted substrates (acrylic or alkyd-based).
- Interior and exterior floor;
 - All types of tiles,
 - Hard vinyl flooring,
 - Wooden substrates,
 - Metal substrates,
- Please consult us for all other application substrates.

■ Application properties

- Time to wait for tile application on **weber.prim TG 5**: 4 hours.
- Drying period: 1 - 4 hours.

■ Conditions of application

- The ambient temperature: +5 °C and +35 °C.
- Avoid application in very hot and/or very damp weather.
- The substrate should be completely dry.

■ Preparation of substrates

- The substrate should be clean, dry and smooth.
- The substrate should be cleaned out plaster, paint, glue, oil, cement residuals completely.
- The substrate should be washed with water and left to dry.
- Lacquer, beeswax and similar residuals on wooden and parquet substrates should be cleaned by scraping and even with scraper. The substrate should be free from dust.

■ Application

- **weber.prim TG 5** should be mixed until homogenous state is achieved without diluting.
- **weber.prim TG 5** should be applied on the whole substrate with lambskin roller and brush in equal thickness.

■ Attention points

- All tools used for application should be cleaned with water before drying.
- Never add foreign materials.
- To protect the substrate adherence to be provided by **weber.prim TG 5** the substrate should not be contaminated during application.
- Avoid contact with skin and wear gloves during application.

■ Limits of application

- Not applicable on plaster screed, plasterboard and gypsum block.
- Not applicable on constant wet and damp substrates.

■ Consumption

100-110 ml/m²,
(For 1 mm thickness).

■ Packaging

Net 4,2 l bucket.

■ Color

Pink.

■ Application tools

Lambskin roller, brush.

■ Shelf life

1 year as of the production date in dry and moisture-free environment provided that packages will not be opened. Package should be kept tightly closed when not in use.

> The stated times apply for 20 °C substrate and ambient temperature and increase at lower temperatures and decrease at high temperatures.

> **Saint-Gobain Weber Yapı Kim. San. ve Tic. A.Ş.** is not responsible for the application errors arising from use of product beyond its intended purpose or failure to comply with the foregoing application conditions and advice on the product.



Saint-Gobain Weber
Yapı Kimyasalları San. ve Tic. A.Ş.
Ankara Karayolu 26. Km.
35171 Kemalpaşa • İzmir • Türkiye

Tel : +90 (232) 397 07 00
Fax : +90 (232) 397 08 00
www.weber.com.tr
info@weber.com.tr



Weber products are produced at ISO 9001:2008 Quality Management System Certified production facilities.