

# weber.prim V (Superflex V)

## Synthetic based primer

### ■ Description

Synthetic resin based, solvent-containing, transparent, ready-to-use primer for **weber.dry FDF** applications on bitumen, metal and fiber cement based substrates.

### ■ Advantages

- Application as primer for **weber.dry FDF**.
- Applicable on metal, bitumen and fiber cement substrates.
- Transparent and ready-to-use structure.

### ■ Range of application

- Used for preparation of bitumen, metal and fiber cement based substrates where **weber.dry FDF** shall be applied.

### ■ Application substrates

- Bitumen based substrates,
- Metal (zinc and aluminum) substrates,
- Fiber cement based substrates,
- Please consult us for other application substrates.

### ■ Performance

- Color: Transparent
- Density: approx. 1,0 kg/dm<sup>3</sup>

### ■ Conditions of application

- Ambient temperature: over +5 °C.

### ■ Preparation of substrates

- Substrates should be clean, smooth, sound and free from adhesion diminishing residues like form oil and loose materials.

### ■ Application

- **weber.prim V** should be applied to bitumen, metal and fiber cement based substrates, where **weber.dry FDF** shall be applied, with the help of a brush, roller or spray and without being diluted.
- It should be ensured that the solvent in the product is completely evaporated prior to the applications on **weber.prim V**.

### ■ Attention points

- No foreign object should ever be added.
- All tools used for application should be cleaned up with thinner after use before they dry.

### ■ Packaging

Net 18 lt and 5 lt tin.

### ■ Application tools

Brush, roller, spray.

### ■ Shelf life

1 year from the production date in dry and moisture-free ambient.

Package should be kept tightly closed when not in use.

> The stated times apply for 20 °C substrate and ambient temperature and increase at lower temperatures and decrease at high temperatures.

> **Saint-Gobain Weber Yapı Kim. San. ve Tic. A.Ş.** is not responsible for the application errors arising from use of product beyond its intended purpose or failure to comply with the foregoing application conditions and advice on the product.



Saint-Gobain Weber  
Yapı Kimyasalları San. ve Tic. A.Ş.  
Ankara Karayolu 26. Km.  
35171 Kemalpaşa • İzmir • Türkiye

Tel : +90 (232) 397 07 00  
Fax : +90 (232) 397 08 00  
www.weber.com.tr  
info@weber.com.tr



Weber products are produced at ISO 9001:2008 Quality Management System Certified production facilities.

