

# weber.prim XR

## Façade primer

### ■ Description

Acrylic emulsion-based, façade primer with fillings.

### ■ Range of application

- Applied as a primer on substrates especially with high porosity and absorptivity of which are high in exterior walls of buildings, under the paint and coating, for the purpose of increasing adherence and water-repellent feature and reducing consumption of final layer paint and coating.

### ■ Application substrates

- Cement based renders,
- Concrete (**weber.tec R**, **weber tec RK**, or **weber.tec RM** applied),
- Gas concrete (**weber.tec GB** applied),
- Please consult us for all other application substrates.

### ■ Application

- **weber.prim XR** is diluted in the ratio of 5/1 (**weber.prim XR** /water) and mixed until it reaches a homogenous state and is applied as one layer with lambskin roller or brush.
- Paint or coating application should be started at least 12 hours after the application of **weber.prim XR**.  
**Note:** Diluted **weber.prim XR** should be mixed and kept in homogenous state, and it should not deposit.

### ■ Limits of application

Not applicable on wet and damp substrates.

### ■ Consumption

8-11 m<sup>2</sup>/l (for single coat).

### ■ Packaging

Net 15 l. buckets.

### ■ Color

5 colors.

### ■ Application tools

Lambskin roller, brush.

### ■ Shelf life

1 year as of the production date in dry and moisture-free environment provided that packages will not be opened. Package should be kept tightly closed when not in use. Package should be protected against frost.

> The stated times apply for 20 °C substrate and ambient temperature and increase at lower temperatures and decrease at high temperatures.

> **Saint-Gobain Weber Yapı Kim. San. ve Tic. A.Ş.** is not responsible for the application errors arising from use of product beyond its intended purpose or failure to comply with the foregoing application conditions and advice on the product.



Saint-Gobain Weber  
Yapı Kimyasalları San. ve Tic. A.Ş.  
Ansızca köyü Ansızca İç Kısım San. Sok. No: 284  
35171 Kemalpaşa - İzmir - Türkiye

Tel : +90 (232) 397 07 00  
Faks : +90 (232) 397 08 00  
www.weber.com.tr  
info@weber.com.tr



Weber products are  
produced at ISO 9001 –  
ISO 14001 – OHSAS 18001  
Management System  
Certified production facilities.

