

weber.prim XT

Silicone added faade primer

■ Description

Acrylic emulsion-based, silicone added, faade primer with fillings.

■ Range of application

- Applied as a primer on substrates especially with high porosity and absorptivity of which are high in exterior walls of buildings, under the silicon-added paint and coating, for the purpose of increasing adherence and water-repellent feature and reducing consumption of final layer paint and coating.

■ Application substrates

- Cement based renders,
- Concrete (**weber.tec R**, **weber tec RK** or **weber.tec RM** applied),
- Gas concrete (**weber.tec GB** applied),
- Please consult us for all other application substrates.

■ Application

- **weber.prim XT** is diluted in the ratio of 5/1 (**weber.prim XT** /water) and mixed until it reaches a homogenous state and is applied as one layer with lambskin roller or brush.
- Paint or coating application should be started at least 12 hours after the application of **weber.prim XT**.
Note: Diluted **weber.prim XT** should be mixed and kept in homogenous state, and it should not deposit.

■ Limits of application

Not applicable on wet and damp substrates.

■ Consumption

8-11 m²/lt (for single coat).

■ Packaging

Net 15 lt buckets.

■ Color

5 colors.

■ Application tools

Lambskin roller, brush.

■ Shelf life

1 year as of the production date in dry and moisture-free environment provided that packages will not be opened. Package should be kept tightly closed when not in use. Package should be protected against frost.

➤ The stated times apply for 20 °C substrate and ambient temperature and increase at lower temperatures and decrease at high temperatures.

➤ **Saint-Gobain Weber Yapı Kim. San. ve Tic. A.Ş.** is not responsible for the application errors arising from use of product beyond its intended purpose or failure to comply with the foregoing application conditions and advice on the product.



Saint-Gobain Weber
Yapı Kimyasalları San. ve Tic. A.Ş.
Anısızca köyü Anısızca İç Kısım San. Sok. No: 284
35171 Kemalpaşa • İzmir • Türkiye

Tel : +90 (232) 397 07 00
Faks : +90 (232) 397 08 00
www.weber.com.tr
info@weber.com.tr



Weber products are
produced at ISO 9001 –
ISO 14001 – OHSAS 18001
Management System
Certified production facilities.

