

weber.prim extra

Façade primer

■ Description

Pliolite resin-based, transparent ready to apply façade primer.

■ Range of application

- Applied as a primer on façades of building on especially old and dusting substrates for the purposes of preventing dusting and increasing adherence.

■ Application substrates

- Cement based renders,
- Concrete (**weber.tec R**, **weber tec RK**, or **weber.tec RM** applied),
- Gas concrete (**weber.tec GB** applied),
- Please consult us for all other application substrates.

■ Application properties

- Drying time: Min. 12 hours.

■ Conditions of application

- Ambient temperature is between 0 °C and +30 °C.

■ Application

- **weber.prim extra** is mixed until it reaches a homogenous state without diluting and should be applied as one layer with lambskin roller or brush.
- Application of final layer paint in selected type or primer before coating (**weber.prim EG**, **weber.prim XR**, **weber.prim XT**) should be started at least 12 hours after the application of **weber.prim extra**.

■ Attention points

- All tools used for application should be cleaned with water before drying.
- Do not come close with fire.

■ Consumption

10-14 m²/lt (for single coat).

■ Packaging

15 lt buckets.

■ Color

Transparent.

■ Application tools

Lambskin roller, brush.

■ Shelf life

1 year as of the production date in dry and moisture-free environment provided that packages will not be opened. Package should be kept tightly closed when not in use.

➤ The stated times apply for 20 °C substrate and ambient temperature and increase at lower temperatures and decrease at high temperatures.

➤ **Saint-Gobain Weber Yapı Kim. San. ve Tic. A.Ş.** is not responsible for the application errors arising from use of product beyond its intended purpose or failure to comply with the foregoing application conditions and advice on the product.



Saint-Gobain Weber
Yapı Kimyasalları San. ve Tic. A.Ş.
Ansızca köyü Ansızca İç Kısım San. Sok. No: 284
35171 Kemalpaşa • İzmir • Türkiye

Tel : +90 (232) 397 07 00
Faks : +90 (232) 397 08 00
www.weber.com.tr
info@weber.com.tr



Weber products are
produced at ISO 9001 –
ISO 14001 – OHSAS 18001
Management System
Certified production facilities.

