

weber.prim klasik

Acrylic emulsion based primer

■ Description

Acrylic-based, ready to use transparent primer.

■ Advantages

- Ensures smooth appearance before paint application on interior wall.
- Improves resistance of surfaces.

■ Range of application

- Used as the primer under the synthetic and water-based paints in internal and exterior walls of surfaces especially on high-absorbing substrates to increase adherence and reduce final coat paint consumption.

■ Application substrates

- Cement based renders,
- Concrete (**weber.tec R**, **weber.tec RK** or **weber.tec RM** applied),
- Gas concrete (**weber.tec GB** applied),
- Old painted substrates,
- Please consult us for all other application substrates.

■ Conditions of application

- Ambient temperature is between +5 °C and +30 °C.
- Avoid application in very damp and/or hot weather.

■ Application

- **weber.prim klasik** should be diluted in 1/5 (**weber.prim klasik**/water) and mixed until a homogenous status is achieved and applied as single coat with lambskin roller or brush.
- Paint application should be started at least 6 hours after **weber.prim klasik** application.

NOTE: The dilution ratio of **weber.prim klasik** should certainly be applied.

■ Consumption

15-25 m²/l (For single layer).

■ Packaging

15 l. plastic bucket.

■ Colour

Transparent.

■ Application tools

Lambskin roller, brush.

■ Shelf life

1 year as of the production date in dry and moisture-free environment provided that packages will not be opened. Package should be kept tightly closed when not in use. Package should be protected against frost.

> The stated times apply for 20 °C substrate and ambient temperature and increase at lower temperatures and decrease at high temperatures.

> **Saint-Gobain Weber Yapı Kim. San. ve Tic. A.Ş.** is not responsible for the application errors arising from use of product beyond its intended purpose or failure to comply with the foregoing application conditions and advice on the product.



Saint-Gobain Weber
Yapı Kimyasalları San. ve Tic. A.Ş.
Anısızca köyü Anısızca İç Kısım San. Sok. No: 284
35171 Kemalpaşa • İzmir • Türkiye

Tel : +90 (232) 397 07 00
Faks : +90 (232) 397 08 00
www.weber.com.tr
info@weber.com.tr



Weber products are
produced at ISO 9001 –
ISO 14001 – OHSAS 18001
Management System
Certified production facilities.

