

# weber.tec 902 (Plastikol 4 V)

## Bitumen based primer

### ■ Description

Bitumen based, one-component, ready-to-use primer with solvent.

### ■ Advantages

- Suitable for bitumen membrane substrates.
- Applicable on dry and slightly moist substrates.

### ■ Range of application

- Used as a primer prior to the application of bitumen membranes on reinforced concrete substrates and prior to the application of **weber.tec 911** and **weber.tec 905** on old bitumen membranes.

### ■ Application substrates

- Cement based substrates,
- Old bitumen membranes,
- Please consult us for other application substrates.

### ■ Performance

- Color: Black
- Dry residue: 38 %
- Density: 0,9 kg/dm<sup>3</sup>

### ■ Conditions of application

- Ambient temperature: over +1 °C.

### ■ Preparation of substrates

- Substrates should be dry or slightly moist, frost-protected and free from residues such as oil, dust.

### ■ Application

- **weber.tec 902** should be applied to substrate with the help of a brush, roller or spray and without being diluted.
- It should be ensured that the solvent in the product is completely evaporated prior to the applications on **weber.tec 902**.

### ■ Attention points

- No foreign object should ever be added.
- All tools used for application should be cleaned up with thinner after use before they dry.

### ■ Limits of Application

- Not applicable on metal substrates that do not contain iron such as aluminum and zinc.

### ■ Consumption

165-335 ml/m<sup>2</sup> depending on absorption of substrate.

### ■ Packaging

Net 12 lt tin.

### ■ Application tools

Brush, roller, spray.

### ■ Shelf life

1 year from the production date in dry and moisture-free ambient.  
Package should be kept tightly closed when not in use.

> The stated times apply for 20 °C substrate and ambient temperature and increase at lower temperatures and decrease at high temperatures.

> **Saint-Gobain Weber Yapı Kim. San. ve Tic. A.Ş.** is not responsible for the application errors arising from use of product beyond its intended purpose or failure to comply with the foregoing application conditions and advice on the product.



Saint-Gobain Weber  
Yapı Kimyasalları San. ve Tic. A.Ş.  
Ankara Karayolu 26. Km.  
35171 Kemalpaşa • İzmir • Türkiye

Tel : +90 (232) 397 07 00  
Fax : +90 (232) 397 08 00  
www.weber.com.tr  
info@weber.com.tr



Weber products are produced at ISO 9001:2008 Quality Management System Certified production facilities.