

weber.tex SFLEX (Serpo Flex)

UV-cured, elastomeric, grained façade paint

■ Description

UV-cured, not losing its flexibility between -40 °C and 60 °C, elastomeric, grained façade paint.

■ Advantages

- Easy and fast application.
- Resistance to external factors.
- Allows the substrate to breath.

■ Range of application

- Applied as the grained paint on façades of all buildings.

■ Application substrates

- Exterior walls;
 - Cement based renders,
 - Concrete (**weber.tec R**, **weber tec RK** or **weber.tec RM** applied),
 - Gas concrete (**weber.tec GB** applied),
- Please consult us for all other application substrates.

■ Performance

- Alkaline resistance: in conformity with TS 4320, TS 4321 and TS 4317.
- Resistance to water: in conformity with TS 4320, TS 4321 and TS 4317.
- Scrubbing resistance: in conformity with TS 4970.
- Hiding power: in conformity with 4315.
- pH: 8-9.

These values were obtained as a result of laboratory tests and they are valid for performance of finished applications at the end of drying time. Values may vary due to differences in ambient of jobsites.

■ Reference standards

- TS 5808.

■ Application properties

- Drying time: between 6-24 hours.

■ Conditions of application

- Ambient temperature is between +5 °C and +30 °C.
- Avoid application in very damp and/or hot weather.
- It should not be used on substrates which are frozen or melting or have the risk of frost within 24 hours.

■ Preparation of substrate

- The substrate should be clean, dry, smooth and sound.
- The substrate should be primed with single coat **weber.tex SFLEX** diluted in the ratio of 30 % with water and application of **weber.tex SFLEX** should be started after at least 6 hours.
- The substrates on which **weber.tec RM** has been applied should be primed as single layer with **weber.prim saten** without diluting and primed with **weber.tex SFLEX** diluted with water in the ratio of 30 % and application of **weber.tex SFLEX** should be started at least 6 hours later.

■ Application

- **weber.tex SFLEX** is applied in one layer without diluting and via lambskin roller on the whole substrate.

■ Attention points

- To avoid tonality differences, the products which have the same BATCH NUMBER and PRODUCTION DATE should be used at each façade.
- Exterior wall should be protected or application should not be performed in rainy season, rainy days or if rain is expected after the application.
- Water adjustment in very strong wind or working under direct sunlight in very hot days should be noticed and application time should be considered. Large areas should be divided in sections with tapes or application should not be done.
- Never use salty water, lime and similar foreign substances.
- All tools used for application should be cleaned with water before drying.

■ Limits of application

- Not applicable on horizontal and inclined substrates with an angle less than 45 degrees.
- Not applicable on wet and damp substrates.

■ Consumption

0,5 kg/m² (Including prime).

■ Packaging

Net 25 kg buckets.

■ Color

400 colors.

■ Application tools

Lambskin roller.

■ Shelf life

1 year as of the production date in dry and moisture-free environment provided that packages will not be opened. Package should be kept tightly closed when not in use. Package should be protected against frost.

FOR INFO

> The stated times apply for 20 °C substrate and ambient temperature and increase at lower temperatures and decrease at high temperatures.

> **Saint-Gobain Weber Yapı Kim. San. ve Tic. A.Ş.** is not responsible for the application errors arising from use of product beyond its intended purpose or failure to comply with the foregoing application conditions and advice on the product.



Saint-Gobain Weber
Yapı Kimyasalları San. ve Tic. A.Ş.
Ansızca köyü Ansızca İç Kısım San. Sok. No: 284
35171 Kemalpaşa • İzmir • Türkiye

Tel : +90 (232) 397 07 00
Faks : +90 (232) 397 08 00
www.weber.com.tr
info@weber.com.tr

