

weber.tex gotik

Thick-textured façade coating

■ Description

Acrylic emulsion-based, thick-textured façade coating.

■ Advantages

- Applicable on external thermal insulation systems.
- Allows the substrate to breath.
- Resistant to external factor.

■ Range of application

- Applied as a final coating on exterior thermal insulation systems and on façades of all buildings.

■ Application substrates

- Exterior walls;
 - Cement based renders,
 - Concrete (**weber.tec R**, **weber tec RK**, or **weber.tec RM** applied),
 - Gas concrete (**weber.tec GB** applied),
- Please consult us for all other application substrates.

■ Performance

- Peeling resistance:
 - In dry state > 2,5 kgf
 - At the end of wetting-drying: > 2 kgf
 - After frosting- thawing: > 2 kgf
- Water absorption property: < 0,5 kg (cm²h^{0,5})
- pH: 8-9
- Water vapor permeability: > 0,5 m⁻¹

These values were obtained as a result of laboratory tests and they are valid for performance of finished applications at the end of drying time. Values may vary due to differences in ambient of jobsites.

■ Reference standards

- TS 7847.

■ Application properties

- Drying time: between 12-24 hours.

■ Conditions of application

- Ambient temperature is between +5 °C and +30 °C.
- Avoid application in very damp and/or hot weather.
- It should not be used on substrates which are frozen or melting or have the risk of frost within 24 hours.

■ Preparation of substrate

- The substrate should be clean, dry, smooth and sound.
- The substrate should be primed with **weber.prim EG** diluted in the ratio of 1/1 (**weber.prim EG**/water) and application of **weber.tex gotik** should be started after at least 12 hours.
- The prime application should be done with the prime having the proper color for **weber.tex gotik**.

■ Application

- In order not to form any joints in wide substrates and color transitions to be compatible, 20 m² areas should be determined with paper tapes.
- **weber.tex gotik** should be spread on the substrate with plastic trowel or perforated roller uniquely. The perforated roller should be saturated with the material before the application.
- While **weber.tex gotik** is still wet, pattern should be achieved from top to bottom with perforated roller. You should be careful about not to fill the roller excessively or drying for the pattern not to deteriorate.
- Adhesive tapes should be removed carefully before **weber.tex gotik** hardens.

■ Attention points

- To avoid tonality differences, the products which have the same BATCH NUMBER and PRODUCTION DATE should be used at each façade.
- Exterior wall should be protected or application should not be performed in rainy season, rainy days or if rain is expected after the application.
- Water adjustment in very strong wind or working under direct sunlight in very hot days should be noticed and application time should be considered. Large areas should be divided in sections with tapes or application should not be done.
- Never use salty water, lime and similar foreign substances.
- All tools used for application should be cleaned with water before drying.

■ Limits of application

- Not applicable on horizontal and inclined substrates and with an angle less than 45 degrees.
- Not applicable on wet and damp substrates.

■ **Consumption**

1,8-2,0 kg/m².

■ **Packaging**

Net 25 kg buckets.

■ **Color**

400 colors.

■ **Application tools**

Perforated and coral roller.

■ **Shelf life**

1 year as of the production date in dry and moisture-free environment provided that packages will not be opened. Package should be kept tightly closed when not in use. Package should be protected against frost.

FOR INFO

> The stated times apply for 20 °C substrate and ambient temperature and increase at lower temperatures and decrease at high temperatures.

> **Saint-Gobain Weber Yapı Kim. San. ve Tic. A.Ş.** is not responsible for the application errors arising from use of product beyond its intended purpose or failure to comply with the foregoing application conditions and advice on the product.



Saint-Gobain Weber
Yapı Kimyasalları San. ve Tic. A.Ş.
Ansızca köyü Ansızca İç Kısım San. Sok. No: 284
35171 Kemalpaşa • İzmir • Türkiye

Tel : +90 (232) 397 07 00
Faks : +90 (232) 397 08 00
www.weber.com.tr
info@weber.com.tr



Weber products are
produced at ISO 9001 –
ISO 14001 – OHSAS 18001
Management System
Certified production facilities.

